



SHJ

Snow plough



The SHJ is a very special single body side plough for trucks and is the only side plough in the world with ploughing speed up to 90 km/h. Designed especially for highways, the SHJ ensures the cleanest ploughing quality in any conditions due to the iFlex flexible blade system. Designed to cope with the severest conditions, the SHJ's ultra-strong steel plough wing provides first-rate stability, despite the considerable ploughing forces experienced at high speed and in severe weather conditions. The iFlex is also the best solution in the market to combat noise pollution while clearing high-friction surfaces such as slushy roads.

Highlights

- The SHJ side plough has an **attack angle of 42° to 51°** depending on the model. This angle is perfect to cut ice and snow from the road surface as sharply as a knife, without floating on frozen snow and ice. On top of the excellent cleaning result, this “aggressive” angle does not harm road markings and runs smoothly over obstacles, such as manhole covers, when equipped with the iFlex blade system.
- A **simple and user-friendly “plug and play” attachment** to the truck's frame does away with the need for any tools or external lifting devices, while the SHJ has an adjustable storage leg as a standard to ease mounting and de-mounting. These features allow operators to react quickly to changing conditions.
- The rounded **shape of the wing**, together with the **polyurethane visor, ensures that snow flies effectively from the plough** and, due to its high snow ejecting properties, snow bank accumulation is significantly lower.

Your benefits

- **Reduced fuel consumption:** Best attack angle boosts aerodynamic rolling of the snow in maximum ploughing speed up to 90 km/h.
- **Easy and safe:** Several safety systems, powerful hydraulics and stepless ploughing width adjustment.
- **Side plough you can trust:** Reliability ratio - which measures reliability of the side plough while ploughing - meets the highest standards.
- **Just plug and play:** easy to attach without any tools or lifting devices.

We know how important it is that your machines and equipment are always ready to deploy. **Get in touch with us** about our range of tailored services and original spare parts.





Using digital solutions to monitor, control and optimise your operations? Saving fuel and resources? With reduced CO₂ emissions and increased security? **Get in touch with us.** We'll make it work.

Performance features

Side plough wing

Smaller side plough models have a fixed blade with an attack angle of 42°. Larger ones are mostly used on highways and can be equipped with the iFlex blade system with a less aggressive attack angle of 51°. The iFlex blade system consists of one-foot elements which precisely follow the road surface, as well as providing an outstanding ploughing result on impacted snow and roads with tracks or potholes. The wing structure is made of ultra-strong steel.



Snow bank cutting

The plough wing was originally designed for use not only with trucks, but for graders at snow bank cutting works. Nowadays, snow cutting is needed on graveled roads with high snow banks during the spring. The SHJ is ideal for cutting snow on the same level as the road surface. However, it can be tilted downwards into a negative inclination angle to move snow at the very bottom of the road bank.

SHJ J side ploughs: Flexible blade system

The SHJ J range consists of two different wing sizes, 16 and 18 feet, which differ from standard side ploughs thanks to the flexible iFlex blade which follows the contours of the road surfaces precisely, while preventing vibration passing onto the wing and back to the base truck. The SHJ J side plough models complement the low-noise front ploughs, significantly reducing the noise of the entire road maintenance unit. The iFlex blade is divided into 305 mm long flexible sections, which gives the side plough an excellent ploughing result over the entire wing. The working width of the wing can be readily adjusted while driving.

Attachment system

By being attached to the truck's subframe in two places and connected with a longitudinal beam, the force is distributed evenly along the frame to ensure better handling of the truck during ploughing.

The SHJ side plough attachment system is very compact in terms of necessary space and consists of two parts – a front attachment requiring 300mm of space into the wheel base and a rear attachment requiring 200mm space at the rear of the subframe. On one hand this ensures optimum force distribution along the whole subframe, on the other it leaves space to have additional equipment mounted within the wheel base, such as a scraper or underbody brush.

All side plough wings with attachments are designed so that they will work together in perfect harmony with scrapers.

Rear attachment has models with integrated underrun beam.



Protection systems

Safety protection of the plough starts with a hydraulic safety valve integrated into a swiveling cylinder. In the case of overloading caused by a collision, the shock valve releases oil back to the tank and the wing moves back towards the truck. At the same time, the longitudinal beam has a safety pin which cuts away for rapid wing closing, while the beam itself will absorb the impact and bend to an "S" shape to take the impact energy. All these stages of protection aim to save the truck's frame as this is the most expensive element.



Snow visor

The snow visor is made from robust and flexible polyurethane and continues the wing's cylinder shape. It helps to roll snow inside of the wing and eject it quickly with the help of aerodynamic forces. This prevents snow obscuring the driver's windshield and mirrors, making ploughing safe, comfortable and relatively risk-free.



Warning lights system AM PRO



Over the years, a reliable, powerful, and safe warning light system has been developed together with road authorities, police and drivers to make use of the side plough as safe as possible for all road users. Today's system consists of three beacons, five strobe lights and one red marking light at the end of the wing. Experience of use of this system in many countries has shown a dramatic drop in accidents involving other road users.

Accessories

- Wear disk support
- Gel-filled wheel support
- AM PRO warning light system
- iFlex blade system for highway models
- Noise reduction set
- Steel blade set
- Hard metal blade set



Gallery



Variants

SHJ 210



SHJ 212



SHJ 214



SHJ 216 J



SHJ 218 J



Related products

HPD

Snow plough



RMT

Road maintenance truck



SHJ TR

Snow plough





Trust in our many years of uniquely diverse experience. **Get in touch with us.** We'll find the right solution for your specific challenge.

Technical data

	SHJ 210	SHJ 212	SHJ 214
Construction			
Attack angle of the blade	42°	42°	42°
Swiveling angle	3° - 48°	3° - 48°	3° - 48°
Dimensions			
Plough height right	1,370 mm	1,370 mm	1,370 mm
Plough height left	550 mm	550 mm	550 mm
Length at cutting edge	3,050 mm	3,660 mm	4,270 mm
Working width max.	2,270 mm	2,730 mm	3,180 mm
Weights			
Approx. weight with steel cutting edges	1,100 kg	1,200 kg	1,250 kg

	SHJ 216 J	SHJ 218 J
Construction		
Number of iFlex blades (if equipped)	16	18
Attack angle of the blade	42° / 51°	42° / 51°
Swiveling angle	2° - 46°	2° - 46°
Dimensions		
Plough height right	1,370 mm	1,370 mm
Plough height left	550 mm	550 mm
Length at cutting edge	4,880 mm	5,490 mm
Working width max.	3,510 mm	3,950 mm
Weights		
Approx. weight with steel cutting edges	1,300 kg	1,450 kg



© Aebi Schmidt Group
www.aebi-schmidt.com

Aebi Schmidt Holding AG
CH-8050 Zurich, Switzerland

All rights reserved. Technical data is subject to change.
Illustrations are not binding. Errors and amendments excepted.

Document created on 9 JUN 2024

